



Information requirement for RVUs as per EU Regulation No. 1254/2014 Heat Recovery Unit Zehnder ComfoAir 155 CM

| Heat Recovery Unit Zennder ComfoAir 155 CM | | | | | | | | | | | | |
|--|-----------------------------------|-------|-------|-----------------------------------|-------|-------|-----------------------------------|-------|-------|-----------------------------------|-------|-------|
| Supplier's Name or Trade Mark | Zehnder Group | | |
| Supplier's Model Identifier | CA155CM-GB | | | CA155CM-GB | | | CA155CM-GB | | | CA155CM-GB | | |
| SEC in [kWh/(m²a)] Specific Energy Consumption (Cold, Average, Warm) | -80.6 | -41.8 | -17.0 | -81.2 | -42.4 | -17.4 | -82.5 | -43.3 | -18.3 | -84.8 | -45.1 | -19.7 |
| SEC Class | A+ | Α | Е | A+ | Α | Е | A+ | Α | Е | A+ | A+ | Е |
| Type of Ventilation Unit | Bidirectional RVU | | |
| Type of Drive Installed | Variable Speed | | |
| Type of Heat Recovery System | Recuperative | | | Recuperative | | | Recuperative | | | Recuperative | | |
| Thermal Efficiency [%] | 91 | | | 91 | | | 91 | | | 91 | | |
| Maximum Flow Rate in [m³/h] / [l/s] | 278 / 77 | | | 278 / 77 | | | 278 / 77 | | | 278 / 77 | | |
| Electric Power Input [W] | 152 | | | 152 | | | 152 | | | 152 | | |
| Sound Power Level [dB(A)] | 46 | | | 46 | | | 46 | | | 46 | | |
| Reference Flow Rate in [m³/h] / [l/s] | 195 / 54 | | | 195 / 54 | | | 195 / 54 | | | 195 / 54 | | |
| Reference Pressure Difference [Pa] | 50 | | | 50 | | | 50 | | | 50 | | |
| SPI [W/(m³/h)] | 0.31 | | | 0.31 | | 0.31 | | | 0.31 | | | |
| Control Factor and Typology | 1 Manual Control | | | 0.95 Clock-Controlled | | | 0.85 Central Demand Control | | | 0.65 Local Demand Control | | |
| Declared Maximum Internal and External Leakage Rates [%] | Internal: 1.2% External: 1.1% | | |
| Mixing Rate | - | | | - | | | - | | | - | | |
| Position and Description of Visual Filter Warning | Details within Homeowner Guide | | |
| Internet Address for Assembly and Disassembly Instructions | www.zehnder.co.uk | | | www.zehnder.co.uk | | | www.zehnder.co.uk | | | www.zehnder.co.uk | | |
| Airflow Sensitivity to Pressure Variations [%] | - | | | - | | - | | | - | | | |
| Indoor / Outdoor Air Tightness [m³/h] | - | | | - | | | - | | | - | | |
| AEC (kWh/a) Annual Electricity Consumption (Cold, Average, Warm) | 967 | 430 | 385 | 930 | 393 | 348 | 860 | 323 | 278 | 745 | 208 | 163 |
| AHS (kWh/a) Annual Heating Energy Saved (Cold, Average, Warm) | 9026 | 4614 | 2086 | 9054 | 4628 | 2093 | 9110 | 4657 | 2106 | 9222 | 4714 | 2132 |